

| | | |
|---------|-----|-----|
| 基準風速 | * | m/s |
| 設置高さ | * | m |
| 地表面粗度区分 | Ⅲ | |
| 垂直積雪量 | 40 | cm |
| 設計用水平震度 | 1.5 | |

Technical drawing of a three-story building facade showing a grid of columns and beams. The drawing includes dimensions for the overall width (5420) and the spacing between columns (1800, 10, 1800, 10, 1800). The drawing also shows the structural details of the columns and beams, including reinforcement bars and joints. The drawing is a cross-section view of the building facade.

太陽電池モジュール
 (※型番は左下参照)

ブレース材
 (C-60*30*10*2.3t)

2300

1100

65

1100

65

1100

(3t)

[illegible]

| | | | | | | | | | | | | | | | | | | |
|----|---|---|---|------|-----|----|---|---|---|-----|--------------|----|------------|----|------------------------------------------------------------------------------------------------|----|------------|----|
| △ | | | | | | | | | | 作成日 | | | 2024.06.28 | |  三洋工業株式会社 | 図名 | 仕様図面 | |
| △ | | | | | | | | | | 尺度 | 1/40 (A3) | 図法 | 三角法 | 単位 | | | mm | 員数 |
| △ | | | | | | | | | | 承認 | | 審査 | | 製図 | | | 設計 | 図番 |
| △ | | | | | | | | | | | | | | | | | | |
| △ | | | | | | | | | | | | | | | | | | |
| △ | | | | | | | | | | | | | | | | | | |
| 符号 | 年 | 月 | 日 | 訂正記事 | 訂正者 | 部番 | 部 | 品 | 名 | 材 | 料 | 重 | 量 | 備 | 考 | | GSa513266S | |

三洋工業株式会社

| | |
|----|-------------------------|
| 図名 | 仕様図面 |
| 図番 | 3段 3列 20度 GSa513266S |